lihtan.net - published 2023 NOV 24

DIRECT PROGRAMMING OF THE BIOFIELD TO MITIGATE HARMFUL RADIATION

Emmanuel Fischer

ABSTRACT

Many spiritual traditions include energetic exercises that are designed to structure and strengthen the human aura. People have long worn amulets and talimans since the time of antiquity for purposes of providing personal protection. The tradition of geomancy has been used for thousands of years to provide energetic protection to buildings, and to facilitate the creation of sacred space inside of temples. These processes have been rediscovered in modern times to address the problems from exposure to harmful EMF radiation. I started with the hypothesis that since my biofield is capable of behaving like a forcefield¹, why not deliberately encode it with the information it needs, so that it can transmute radiation?

In experiments I've conducted, I've determined that it's possible to program the human biofield so that it can function like a pendant or harmonizer device. You can receive the same benefits of protection, without having to carry a physical object with you. Unlike physical harmonizers which can become energetically impregnated, and stop working, I've noticed no degradation in performance when my biofield is put to the task of doing energetic transmutation.

INTRODUCTION

When someone wears a protective pendent or talisman, the shape information of it ends up having a geometrical influence on the biofield. A talisman would function vibrationally as a etheric reference signal, very similar to the oscillator in a radio transmitter. If the biofield is receptive to having information impressed upon it, why not get it to retain the information permanently?

BACKGROUND

With my work in geomancy, it's considered a good practice to layer multiple levels or corrections in your environment, to achieve a robust and adaptive protection strategy². For the purposes of this research, I had to remove and disable all of them, so that I could independently evaluate how the biofield could potentially transform energy on it's own.

One device I have in my home is a BioGeometry home cube which blankets the home with a balancing area effect. This can be disabled by setting the device on it's side. All the doors, windows, mirrors, electrical systems and electronic devices are also individually balanced with their own corrections, they don't have an area effect outside of their boundaries. For personal protection, I usually carry a BioGeometry "L90" pendant with me. Removing it sufficient to disable it's balancing influence.

METHODS AND TEST PROCEDURES

During the application of the programming protocol, all the environmental energetic supports were active, so that I could assimilate their energetic configurations.

For my testing, I used a number of calibrated radiesthesia pendulums. One pendulum is calibrated to only detect the resonance of sacred energy sites (BG3). A vertical dial pendulum is calibrated to only detect toxic detrimental energies (VNG). Lastly a neutral pendulum is used for doing measurements involving the personal wavelength (PWL). Calibrated pendulums will spin clockwise on their own when they come into resonance for the vibration they've been calibrated to. The neutral pendulum however has three possible readings. If it remains rocking forward and back in the search pattern, this is a neutral reading. If it spins clockwise (CW), it means the object or it's emissions is beneficial to the person doing the measurement. If it spins counter-clockwise (CCW), it means the object or it's emissions is detrimental to the person doing the measurement.

On my test bench I had a BioGeometry charging plate (which is a strong BG3 producer), a container of ABS pipe cement (a poisonous substance which tests strong for VNG), and finally an uncorrected set of Bluetooth headphones. I also made sure that I didn't have any host devices that the headphones could pair to.

The test begins with checking if the charging plate produces BG3. The headphones are also checked for the absence of BG3 both when they're off, and when powered on. (if the headphones had BG3, it would indicate that they've been balanced, and couldn't be regarded as a hazardous radiation source). The ABS cement is used to confirm vertical pendulum calibration. Most importantly, the neutral pendulum is used to determine if toxic radiation sources are still hazardous to me after I've applied the protocol

RESULTS

The charging plate tested for BG3. The ABS cement tested for VNG. The headphones had no BG3 when it was off. When it was powered on, no BG3 was detected again. VNG was present when they were on and it was trying to locate a host device to connect with. This indicated that these headphones were a toxic radiation source when they were on.

Typically PWL measurements of toxic energy sources will yield a CCW reading from a neutral pendulum. However in my initial tests, I only ever got a neutral reading! This tells me that my biofield is now functioning to some capacity to transmute radiation before it can get to me. I doubled checked my readings. The headphones still produced toxic VNG emissions, but my body didn't recognize it as being harmful!

A video of my initial testing can be seen at this URL: https://www.youtube.com/watch?v=8WW8aj3r-DY

It has now been more than 4 weeks since my initial discovery. I've repeated the tests again, and the results are still the same. My body no longer senses toxic radiation as being a threat.

CONCLUSIONS

In the geomantic products world, there's typically three layers of protection that one can purchase to protect themselves from EMF. The first are whole home devices that have an area effect, and blanket and entire dwelling with protection. The second are individual corrective devices that are attached to electrical and wireless devices. The third are pendants that are worn on the body for personal protection.

What I've done is I've introduced a fourth category of protection that allows the human body to internally generate it's own protection from harmful EMF radiation. Unlike corrections that need to continually purchased for new devices, routinely clear for energetic impregnation, or can fail to protect if they become damaged or go missing, geometric programming of the biofield is something that you carry with you all the time, and shown no signs of fading in it's protective ability.

There are still questions as to whether this protocol will work with people that have a different constituition to their biofield. The use of this method may alter the way people are able to work with and sense subtle energy. In my own case, I can no longer use PWL as a reliable measurement for detecting toxic energy sources. More research needs to be done to see how this would interact with people that perform different types of energy healing, as well as those that have high enough psychic energy, that their biofield can disrupt the operation of electronics.

REFERENCES

- 1. Human Design System, Ra Uru Hu, published by Jovian Archive Pte. Ltd.
- 2. BioGeometry Foundation Training, Dr. Ibrahim Karim, published by BioGeometry Energy Systems Ltd.

info@lihtan.net Lihtan Networks http://lihtan.net